



KC-02
2-Axis Controller for
24VAC Speed Dome



KC-03
3-Axis Controller for 24VAC
Speed Dome

The SA-Series will control all VSG 24VAC Speed Domes. It is capable of controlling up to 32 devices. It can also control Low-Speed Domes, Pan-Tilt devices, fixed Zoom cameras, and various Serial devices.

It uses a built-in RS-485 communication protocol that will control most popular protocols.

For Purchase Locations, contact us at Sales@RealTimeDVRs.COM



Video Security Group SA-Series Professional Joystick Controller

- * Two models, one with a standard joystick, and one that controls zoom by turning the joystick knob
- * Controls up to 32 devices, including Speed Domes, PT Devices, and Serial Devices
- * Pelco Compatible, RS-485 Communication Protocol
- * Numerical keyboard for programming and control
- * One-Touch buttons for Auto-Scan, Preset Scan, Iris, and Focus
- * Supports "Auto Scan" and "Tour Through the Presets"
- * Contact us at info@RealTimeDVRs.COM for more Technical information.....

SPECIFICATIONS

Voltage.....	DC9V, (+/- 20%)
Operating Temperature.....	-10 degrees C to 50 degrees C
BAUD Rate.....	2400, 4800, and 9600 Bits per second
Communication	RS-485
Comm Distance.....	up to 1200 Meters if Daisy-Chained
Device Control	up to 32 Devices
Display.....	LCD display
Joystick	High quality joystick engineering